

TECHNICAL FEATURES SELECTION GUIDE

This is a guide only. Please refer to the product data sheets for full specifications. Certain products are manufactured to order and are subject to MOQs.

Technical Feature	Product Type																		
	C	CLR	CYG	CX3	CTW	CDW 3X	CDW 4X	SHF	End Caps	CM	CM X3	CM X4	SH DR	CK (Kynar)	SV (Viton)	SPTFE (Teflon)	SB	NSH	MA
Data Sheet pdf:																			
General Purpose Use	✓	✓																	
UL Approved	✓	✓		✓	✓	✓	✓			✓	✓	✓							
MIL Spec			✓					✓		✓	✓	✓	✓	✓	✓	✓			✓
Flame Retardant/ Self Extinguishing	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓			
2:1 Shrinkage Ratio	✓	✓	✓		✓			✓		✓			✓	✓	✓			✓	
3:1 Shrinkage Ratio				✓		✓					✓								✓
4:1 Shrinkage Ratio							✓					✓							
Earth Identification			✓																
Clear		✓				✓								✓		✓			
Black	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓			✓	✓
Colours	✓					✓ Red												✓	
Ultra Thin Wall					✓														
Adhesive/Glue Lined						✓	✓		✓										✓
Halogen Free								✓									✓		
Low Smoke								✓											
High Temp Use 150°C													✓						
High Temp Use 175°C														✓					
High Temp Use 200°C															✓				
High Temp Use 250°C																✓			
Diesel Resistant													✓						
Petrol / Fuel Resistant													✓		✓				
Hydraulic/Oil Resistant								✓		✓	✓	✓	✓		✓				
Chemical Resistant														✓	✓	✓			
Solvent Resistant													✓	✓	✓				
Busbar Insulation																	✓		
Non-Slip Textured Finish																		✓	
Medium Wall																			✓
High Electrical Insulation																✓	✓		
Large Diameters >100mm	✓																✓		✓
UV Stabilised	✓ Black					✓ Black	✓ Black	✓	✓						✓				✓
Flexible	✓	✓	✓	✓	✓								✓		✓			✓	
Semi Rigid														✓					
Availability / Lead-Time:	Stock	Stock	Stock	Stock	Stock	Stock	Stock	MOQ 1-5 Days	Stock	MOQ 1-5 Days	MOQ 2-4 Weeks	MOQ 2-4 Weeks	Stock	MOQ 2-4 Weeks	MOQ 2-4 Weeks	MOQ 1-5 Days	MOQ 2-4 Weeks	Stock	MOQ 1-5 Days